

	Metres	Fe
MS (FW)	9.75	32'-
S (FW)	9.52	31'-
INT (FW)	9.41	30'-
W (FW)	9.30	30'-
MS (SW)	9.54	31'-
S (SW)	9.30	30'-
INT (SW)	9.19	30'-
W (SW)	9.08	29'-

Self Unloading Equipment

Two belt gravity system with loop belt elevator. 80 m discharge boom luffing to 18° and slewing to 90° P&S.Shear type basket gates, UHMW plastic linings in holds and vibrators throughout tunnels. Designed discharge rate of up to 5,400 metric tons/hour.

Cargo Deadweight

(610 MT consumables assumed)	Metric	Long
@ Mid Summer	36,800	36,200
@ 26'- 6" (FW) Seaway Draft	28,200	27,750

Note: Deadweight shown excludes Crew & Effects, Fuel Oil, Lube Oil, Water & Stores (~610 MT).

Midship Air Draft

(To Top of Hatch Coaming at Side)

	Metres	Feet
Summer (FW) (9.514 m)	6.53	21'- 6"
Seaway (FW) (8.077 m)	7.97	26'- 2"
Ballast (FW) (5.745 m)	10.31	33'-10"

Hold Capacities (Self-Trim 35°)					
		m³	ft ³		
	Hold 1	7,200	254,300		
	Hold 2	8,800	310,800		
	Hold 3	7,500	264,900		
	Hold 4	9,500	335,500		
	Hold 5	6,500	229,500		
Total, holds and hatches	_	39,500	1,395,000		

Number: 17		
	6.8m x 15.84m	
Туре:	Single plate	
	Metres	Feet
Bow to mid Hatch #1	16.50 m	54'- 2"
Fwd to Aft	165.75 m	543'-10"
Mid Hatch #17 to Stern	43.50 m	142'- 9"

63 Church Street, Suite 600 St. Catharines, Ontario L2R 3C4 Tel: 905.687.7888 Fax: 905.687.7840 www.algonet.com