





Algoma Intrepid



Manager: Algoma Central Corporation
 Registry: Toronto / Canada
 Builder: 3MAJ Uljanik Group, 2019 (Hull 733)
 Type: Great Lakes Bulk Carrier
 Class: Lloyds Register of Shipping
 ✎100A1 Great Lakes & River St Lawrence



Principal Particulars

LOA	198.35 m	650'-09"
LBP	195.29 m	640'-08"
Beam (mld)	23.770 m	78'-00"
Depth (mld)	13.580 m	44'-07"

International (1969) Tonnage

Gross	about	19,851
Net	about	7745

Assigned Drafts (FW)

	Metres	Feet - Inch
Midsummer	9.74	31'-11"
Summer	9.50	31'- 2"
Intermediate	9.38	30'- 9"
Winter	9.25	30'- 4"
Reduction for SW	0.21	8"

Self Unloading Equipment

Two belt gravity system, with single C-Loop & forward-mounted 81.1m boom, which luffs 18° and slews 105° P&S. Feeder gates, UHMW-PE linings in holds, with vibrators fitted throughout. Maximum unloading rate is 5,450 t/hr or 3,750 m³/hr: 5,450 t/hr (stone) or 4,500 t/hr (salt).

Cargo Deadweight

(610 MT consumables assumed)	Metric	Long
@ 31'-11" Mid Summer	31,600	31,100
@ 26'- 6" Seaway Draft	24,100	23,697

Note: Deadweight shown excludes Crew & Effects, Fuel Oil, Lube Oil, Water & Stores (~610 MT).

Midship Air Draft

(To Top of Hatch Coaming at Side)

	Metres	Feet - Inch
Summer (FW)	5.1	16'-8" *
Seaway (FW)	6.52	21'-5" *
Ballast (FW)	8.67	28'-5" **

*less 0.30m IWO 10 & 13
**IWO 13 in Operating Ballast

Hold Capacities (Self-Trim 35°)

	m ³	ft ³
Hold 1	5,200	183,600
Hold 2	9,400	332,000
Hold 3	8,900	314,300
Hold 4	6,500	229,500
Total, holds and hatches	30,000	1,059,400

Hatches

Number:	14
Type:	6.8m (5.1m) x 15.84m Single plate

	Metres	Feet - Inch
Bow to mid Hatch #1	23.16	76'-0"
Fwd to Aft	133.45	437'-10"
Aftmost Hatch to Stern	41.75	137'-0"